#### 2024-SEPT SPECS + PRE-INSTALLATION REQUIREMENTS FOR THE ARDUINO VA358 WHITE EAGLE 2-GROUP "T3"

OFF

#### ELECTRICAL REQUIREMENTS

□ 220 VOLTS / 50 AMPS (7600W / 35A)

□ NEMA L6-50 receptacle①

□ Standard 110 VOLT receptacle within 2' (60cm) of Grinder(s)

### WATER REQUIREMENTS

□ 1/2" dedicated COLD water line with shut-off valve and 3/8" compression fitting 2

□ SHUT-OFF ② MUST ALWAYS BE EASILY ACCESSIBLE IN CASE OF EMERGENCY


□ Water softening is mandatory with hardness >3 GPG (50ppm). Zuccarini installs a BWT in-line water softener 4 but with hardness >12 GPG (200ppm) you must install a central Softening/ Reverse Osmosis (RO) system AND maintain 2-4 BARS water pressure at machine.

SPECS: Water flow rate: 1GPM / TDS: 50-250ppm / Alkalinity: 10-150ppm / Chlorine: <0.50ppm / PH: 6.5-8.5 / Filtration: <1.0 micron

## DRAINAGE REQUIREMENTS

□ Minimum 1.5" (or 3.5 cm) diameter open gravity drain within 3' (1 metre) of machine ③


Drain hose (we provide) must always run DOWN-WARDS (never bending upwards) or it will clog



# COUNTER SPACE REQUIREMENTS

Width: 32.5" (83cm) Height: 20" (51cm)

Depth: 26" (66cm) Weight: 163lb (74kg)



# COUNTER REQUIREMENTS

□ Minimum 2.5" (7cm) in the counter beneath the machine for power supply, cold water & drain hose:

- hole should be directly in the center of the machine or slightly center/back
- IF YOUR COUNTER-TOP IS MADE OF STONE OR METAL, THE HOLE MUST BE DRILLED BEFORE **OUR TECHNICIAN ARRIVES TO INSTALL YOUR MACHINE**

□ Leave space under the counter between cold water shut-off ② and espresso machine for Water Softener④ (max. 30" x 8" x 8" / 75x20x20cm vertical OR horizontal) which must be accessible for regular replacement


#### □ Allow a minimum 4" (10cm) of workspace for Technician beside machine for service access

□ We suggest that you allow a minimum of 8" (20cm) of workspace for Barista in front of machine PLUS space for Espresso Grinder(s) and a Knock Box, etc to be placed on or installed into counter-top beside machine (right or left)

□ The suggested counter height is 36" to 40" (1 metre); if taller, it is suggested you install/place a step or riser for staff to stand on

□ Allow a min. 12" (30cm) clearance above machine

lictoria Arduino MADE IN ITALY



FAILURE TO HAVE SITE PREPARED AT TIME OF INSTALLATION APPOINTMENT WILL CAUSE DELAYS & RESULT IN ADDITIONAL SERVICE & TRAVEL CHARGES.

